NEW BESTORQ LIGHTNING®

V-Belts for the most severe Lawn & Garden applications

LIGHTNING V-belts are created with an outer rubber impregnated fabric cover that is extremely tough, wear resistant and crack resistant. The lowered coefficient outer cover shows extreme resistance to belt turnover or roll- excellent for misaligned drives and if belt is used as a clutch.

- Synthetic rubber throughout and true Kevlar tensile member (don't be mislead by aramid/aramid blend ads)
- Flexible design, but very stable on long drives or misaligned drives
- Conforms to ARPM standard IP-23
- To be used with pulleys made to ARPM standards IP-23 or IP-20
- LAWN & GARDEN V-BELT LIFE TESTING 2017

 400
 350
 250
 200
 150
 100
 50
 test life hrs
 Belts were tested at over rated loads on minimum diameter pulleys, with backside idlers at 3600 RPM

- Made to exceed OEM specifications
- Very resistant to severe and repeated shock loads, and works well on "quarter turn" and "mule" drives
- Great for Lawn & Garden equipment of all types, Ag Equipment and all types of inductrial drives, especially where misalignment clutching or backside idlers are present

Lightning belts are engineered and tested in Lincoln, Nebraska and are backed by over 46 years of professional lawn and garden V-Belt design, testing and application experience.

They are made to have a long shelf life of at least 7 years, when stored out in the sun or stored in temperatures from 40F - 100F.

Available in popular widths 3/8", 1/2", and 5/8" and in the following lenghts:

- 3/8" from 24" to 50"
- 1/2" from 20" to 156"
- 5/8" from 33" to 164"
- many popular half sizes are available

TO ORDER - call, fax or email phone: 877.773.9966 fax: 877.329.8416 orders@Bestorg.com



